


| Anmerkung / REMARKS | |
|---|---|
| b | SPACE REQUIRED FOR MEASURING TORSIONAL VIBRATIONS, AND/OR FOR REMOVAL OF THE VIBRATION DAMPER AND/OR LUBOIL PUMP |
| e | SPACE REQUIRED FOR REMOVAL OF PISTON AND CYLINDER LINER<br>REDUCED REMOVAL HEIGHT PISTON AND LINER 2300mm |
| k | SPACE REQUIRED FOR TERMINAL SET |
| o | SPACE REQUIRED FOR TURBOCHARGER SHAFT |
| p | SPACE TRQUIRED FOR CHARGE AIR COOLER REMOVING |

Gewicht trocken mit flacher Oelwanne
WEIGHT DRY WITH DRY SUMP


CATERPILLAR MOTOREN GmbH & Co. KG RESERVES THE RIGHT TO MODIFY AND AMEND DATA AT ANY TIME. ANY LIABILITY FOR ACCURACY OF INFORMATION PROVIDED IS EXCLUDED.
WE WILL SUPPLY FURTHER BINDING DATA IN CONNECTION WITH A CORRESPONDING ORDER.

ALL RIGHTS RESERVED. NO PART OF THIS PUBLICATION MAY BE REPRODUCED OR COPIED IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF CATERPILLAR MOTOREN GmbH & Co. KG.


| | | | | | |
|---|---|---|---|---|---|
| CATERPILLAR | Modell / Model: 6M25E_FWS 1.0<br>Zeichnung / Drawing: 6M25E_FWS 1.0 | | | | |
| Oberflaechen / Surfaces: ISO 1302 | Allgemeintoleranzen / General Tolerances: ISO 2768 - mK | Drawing Control: W 882 | Massstab / Scale: 1:20 | Gewicht (kg) / Weight (kg): 23.500 | |
| | | Werkstoff / Material | | | |
| Benennung / Name: Motor - Einbauzeichnung<br>ENGINE INSTALLATION DRAWING | | | | | |
| Aend.-Stand / Change Level: - | Freigabe-Nr. / Release No.: | UKZ / Doc. Code: - | Zeichnungs-Nr. / Drawing No.: 6M25E FWS | Blatt / Sheet: 1 | von / of: 1 |