



Cat[®] 323

Hydraulic Excavator

The Cat[®] 323 excavator has the speed, efficiency, and power for your heavy-duty applications requiring maximum productivity. You get built-in Cat GRADE with 2D, Grade Assist, and Payload as standard equipment right from the factory – boosting your operator efficiency by up to 45 percent. Combine these features with a new cab, longer maintenance intervals and reduced fuel consumption that lower maintenance costs by up to 20 percent and fuel consumption by up to 20 percent and you have an absolutely low-cost-per-unit-of-production excavator built for your heavy-duty applications.

Not all features available in all regions. Consult your Cat dealer for specific configurations available in your region.

High Performance with Lower Fuel Consumption

- Use up to 20 percent less fuel than the 323F excavator.
- Increase operating efficiency up to 45 percent with standard Cat Connect technologies that lower operator fatigue and your operating costs, including fuel consumption and daily maintenance.
- The C7.1 engine can run on biodiesel up to B20 and meets U.S. EPA Tier 4 Final and EU Stage IV emission standards with an aftertreatment system that requires no maintenance or downtime.
- The advanced hydraulic system provides the optimum balance of power and efficiency while giving you the control you need for precise digging requirements.
- Match the excavator to the job with power modes; let Smart mode automatically match engine and hydraulic power to digging conditions.
- Auxiliary hydraulic options give you the versatility to use a wide range of Cat attachments.
- Available SmartBoom™ lets the boom freely travel up and down without using any pump flow so operators can focus on stick and bucket work. The benefits are reduced operator stress and reduced fuel consumption.
- Don't let the temperature stop you from working. The excavator has a standard high-ambient temperature capability of 52° C (125° F) and cold start capability of -18° C (0° F). An optional -32° C (-25° F) cold start package is available.

Boost Efficiency and Boost Productivity with Integrated Cat Connect Technologies

- Boost productivity up to 45 percent versus traditional grading with standard Cat GRADE with 2D system – includes indicate-only and laser capability.
 - Dig with guidance to depth, slope, and horizontal distance to grade. You can set up to four different target depth and slope offsets to help save time and money. When the job calls for a different offset, quickly switch through the monitor and get to work.
 - The 2D system is upgradable to Cat GRADE with Advanced 2D or Cat GRADE with 3D.

- Standard Grade Assist:
 - Stay on grade – simply and effortlessly – with single-lever digging.
 - Set your desired bucket angle and let Bucket Assist automatically maintain the angle in sloping, leveling, fine grading, and trenching applications for easy, accurate, and fast jobs.
 - Keep the tracks on ground in lifting and hard digging with Boom Assist.
 - Automatically stop excavator swing at operator-defined set points in truck loading and trenching applications with Swing Assist, which will help you use less effort and consume less fuel.
- Standard Cat PAYLOAD on-board weighing system:
 - Achieve precise load targets and increase loading efficiency with on-the-go weighing and real-time estimates of your payload without swinging.
 - Track your daily productivity such as truck target weights and load/cycle counts.
 - Calibration can be performed in a matter of minutes.
 - Combine Payload with VisionLink[®] and remotely manage your production targets.
- Upgrade to optional Cat GRADE with Advanced 2D:
 - Create and edit grade designs with ease on a second high-resolution 254 mm (10 in) touchscreen monitor.
- Upgrade to optional Cat GRADE with 3D:
 - Create and edit designs with ease and see the front linkage's full range of motion on a second high-resolution 254 mm (10 in) touchscreen monitor.
 - Use the excavator's onboard cell technology to quickly connect to 3D services like Trimble Connected Community or Virtual Reference Station.
 - Know the excavator's exact position relative to GPS and GLONASS systems.
 - The machine automatically compensates for excavator pitch and roll caused by sloping ground conditions.
 - Antennas have theft-prevention bolts; a special tool makes them easy for the owner to remove at the end of a shift.



Cat® 323 Hydraulic Excavator

- Remote Services:
 - Remote Troubleshoot connects you to a dealer service pro to help solve your problem and quickly get you to work.
 - Remote Flash works around your schedule to ensure your machine's software is up to date for optimal performance.
 - The Cat App helps you manage fleet location, hours, and maintenance schedules; it also alerts you for required maintenance and even allows you to request service from your local Cat dealer.
- Standard Product Link™ provides location, machine hours, fuel usage, productivity, idle time, diagnostic codes, and other machine data on demand through VisionLink online interface, helping you improve job site efficiency with lower operating costs.

Work in Comfort in the All-New Cab

- Choose between Deluxe and Premium cabs – both with automatic climate control.
- The Deluxe seat is heated and air adjustable.
- The Premium seat is heated and cooled and adjusts automatically.
- Get in and out of the cab easier using the tip-up left console.
- Advanced viscous mounts reduce cab vibration up to 50 percent over previous excavator models.
- Control the excavator comfortably with easy-to-reach controls all located in front of you.
- Stow your gear with plenty of in-cab storage beneath and behind the seat, overhead, and in the consoles. A cup holder, document holder, bottle holder, and coat hook are also provided.
- Use the standard radio's USB ports and Bluetooth® technology to connect personal devices and make hands-free calls.

Simple to Operate

- Start the engine with a push button; use a Bluetooth key fob, smartphone app, or the unique Operator ID function.
- Program your power mode and joystick preferences using Operator ID; the excavator will remember what you set each time you go to work.
- Navigate quickly on the standard high-resolution 254 mm (10 in) touchscreen monitor, or with the aid of the jog dial control.
- A second 254 mm (10 in) monitor is available for the advanced grade control.
- Not sure how a function works or how to maintain the excavator? Always have the operator's manual at your fingertips in the touchscreen monitor.
- Find the tool you need – even if it's hidden beneath overgrowth or debris. The excavator's onboard Bluetooth reader can search for any work tool equipped with Cat asset tracking devices up to a range of 60 m (200 ft).

Maintenance

- Expect up to 20 percent less maintenance cost than the 323F. (Savings calculated over 12,000 machine hours.)
- Do all daily maintenance at ground level.
- Check engine oil level quickly and safely with the new ground-level engine oil dipstick; fill and check engine oil on top of the machine with a conveniently located second dipstick.
- Track your excavator's filter life and maintenance intervals via the in-cab monitor.
- Do no required maintenance on the Cat Clean Emissions Module.
- Fuel filters are synchronized to be changed at 1,000 hours – double the interval from the previous filters.
- Expect the new air intake filter with precleaner to last up to 1,000 hours – a 100 percent increase over the previous filter.
- The new hydraulic oil filter provides improved filtration performance, anti-drain valves to keep oil clean when the filter is replaced, and longer life with a 3,000 hour replacement interval – 50 percent longer than previous filter designs.
- High-efficiency cooling fans run only when needed; you can program intervals so they automatically reverse to keep cores clean without interrupting your work.
- S-O-SSM ports are on ground level, simplifying maintenance and allowing for quick, easy extraction of fluid samples for analysis.

Safety

- Lift Assist helps you avoid tipping. With visual and auditory alerts, you'll know if your load is within the excavator's safe working range limits.
- The standard 2D E-fence feature integrated right out of the factory prevents the excavator from moving outside operator defined set points.
- Access 100 percent of daily maintenance points from ground level – no need for you to climb on top of the excavator.
- The standard ROPS cab meets ISO 12117-2:2008 requirements.
- Enjoy great visibility into the trench, in each swing direction, and behind you with the help of smaller cab pillars, larger windows, and a flat engine hood design.
- The standard hydraulic lockout lever isolates all hydraulic and travel functions in the lowered position.
- Ground-level shut-off switch stops all fuel to the engine when activated and shuts down the machine.
- A rearview camera and a right-side-view camera are standard. Upgrade to 360° visibility and you'll easily visualize objects and personnel around the excavator in a single view.
- New right-hand service platform design provides easy, safe, and quick access to upper service platform; the service platform steps use anti-skid punch plate to prevent slipping.
- Available boom and stick lowering check valves prevent reverse flow, keeping your front linkage securely in place should the hydraulic system unexpectedly lose power.
- The handrails comply with ISO 2867:2011 requirements.

Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional		Standard	Optional
CAB			BOOM AND STICKS		
ROPS, standard sound suppression (Deluxe only)	✓		5.7 m (18'8") reach boom, 2.9 m (9'6") stick	✓	
ROPS, advanced sound suppression (Premium only)	✓		5.7 m (18'8") HD reach boom, 2.9 m (9'6") HD stick		✓
Air-adjustable seat with heat (Deluxe only)	✓		8.85 m (29'0") super long reach boom, 6.28 m (20'7") stick		✓
Auto-adjustable seat with heat and air ventilation (Premium only)	✓		UNDERCARRIAGE AND STRUCTURES		
High-resolution 254 mm (10 in) LCD touchscreen monitor	✓		600 mm (24") triple grouser shoes		✓
CAT CONNECT TECHNOLOGY			700 mm (28") triple grouser shoes		✓
Cat Product Link	✓		790 mm (31") triple grouser shoes		✓
Cat GRADE with 2D	✓		900 mm (35") triple grouser shoes		✓
Cat GRADE with Advanced 2D		✓	Tie-down points on base frame	✓	
Cat GRADE with 3D		✓	4200 kg (9,300 lb) counterweight		✓
Cat GRADE with Assist	✓		5400 kg (11,900 lb) counterweight	✓	
Cat PAYLOAD	✓		ELECTRICAL SYSTEM		
2D E-fence	✓		Two 1,000 CCA maintenance-free batteries	✓	
Remote Flash capability	✓		Programmable time-delay LED working lights	✓	
Remote Troubleshoot capability	✓		LED chassis light, left-hand/right-hand boom lights, cab lights	✓	
ENGINE			SERVICE AND MAINTENANCE		
Three selectable power modes	✓		Sampling ports for Scheduled Oil Sampling (S-O-S)	✓	
Auto engine idle shutdown	✓		Ground-level and platform-level engine oil dipsticks	✓	
52° C (125° F) high-ambient cooling capacity	✓		SAFETY AND SECURITY		
-32° C (-25° F) cold start capability		✓	Rearview camera	✓	
Double element air filter with integrated precleaner	✓		Right-side-view camera	✓	
Reversing electric cooling fans	✓		360° visibility		✓
Biodiesel capability up to B20	✓		Lift Assist	✓	
HYDRAULIC SYSTEM			Cat asset tracker	✓	
Boom and stick regeneration circuits	✓		Ground-level engine shutoff switch	✓	
Boom and stick lowering check valves		✓	Right-hand handrail and hand hold	✓	
Auto hydraulic warm up	✓		Signaling/warning horn	✓	
Auto two-speed travel	✓				
Boom and stick drift reduction valve	✓				
Hammer return filter circuit		✓			
Advanced Tool Control (two pump, one/two way high-pressure flow)	✓ ¹	✓			
Medium-pressure circuit		✓			
Quick coupler circuit for Cat Pin Grabber	✓ ²	✓			

¹ANZ and Europe only.

²Europe only.

Cat® 323 Hydraulic Excavator

Technical Specifications

Engine

Engine Model	Cat C7.1	
Engine Power – ISO 9249	121 kW	162 hp
Engine Power – ISO 14396	122 kW	164 hp
Bore	105 mm	4 in
Stroke	135 mm	5 in
Displacement	7 L	428 in ³

Hydraulic System

Main System – Maximum Flow (Implement)	429 L/min	113 gal/min
Maximum Pressure – Equipment – Normal	35 000 kPa	5,075 psi
Maximum Pressure – Equipment – Heavy Lift Mode	38 000 kPa	5,510 psi
Maximum Pressure – Travel	34 300 kPa	4,974 psi
Maximum Pressure – Swing	26 800 kPa	3,886 psi

Machine Weight

Operating Weight – 790 mm (31") Shoes	25 500 kg	56,200 lb
• HD reach boom, R2.9 m (9'6") HD stick, 1.38 m ³ (1.81 yd ³) HD bucket, 790 mm (31") triple grouser HD shoes, 5.4 mt (11,900 lb) counterweight.		
Operating Weight – 600 mm (24") Shoes	23 900 kg	52,700 lb
• Reach boom, R2.9 m (9'6") stick, 1.30 m ³ (1.70 yd ³) GD bucket, 600 mm (24") triple grouser HD shoes, 5.4 mt (11,900 lb) counterweight.		

Service Refill Capacities

Fuel Tank	345 L	86.6 gal
Cooling System	25 L	6.6 gal
Engine Oil	25 L	6.6 gal
Swing Drive (each)	5 L	1.3 gal
Final Drive (each)	5 L	1.3 gal
Hydraulic System (including tank)	234 L	61.8 gal
Hydraulic Tank	115 L	30.4 gal
DEF Tank	41 L	10.8 gal

Air Conditioning System

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 0.9 kg of refrigerant which has a CO₂ equivalent of 1.287 metric tonnes.

Dimensions

Boom	Reach 5.7 m (18'8")	
Stick	Reach 2.9 m (9'6")	
Bucket	1.19 m³ (1.56 yd³)	
Shipping Height (top of cab)	2960 mm	9'9"
Handrail Height	2950 mm	9'9"
Shipping Length	9530 mm	31'3"
Tail Swing Radius	2830 mm	9'3"
Track Length	4450 mm	14'7"
Length to Center of Rollers	3650 mm	12'0"
Ground Clearance	470 mm	1'7"
Track Gauge	2380 mm	7'9"
Transport Width – 600 mm (24") Shoes	2980 mm	9'9"
Transport Width – 790 mm (31") Shoes	3170 mm	10'5"
Counterweight Clearance	1050 mm	3'5"

Working Ranges and Forces

Boom	Reach 5.7 m (18'8")	
Stick	Reach 2.9 m (9'6")	
Bucket	1.19 m³ (1.56 yd³)	
Maximum Digging Depth	6720 mm	22'1"
Maximum Reach at Ground Level	9860 mm	32'4"
Maximum Cutting Height	9370 mm	30'9"
Maximum Loading Height	6490 mm	21'4"
Minimum Loading Height	2170 mm	7'1"
Maximum Depth Cut for 2440 mm (8'0") Level Bottom	6550 mm	21'6"
Maximum Vertical Wall Digging Depth	5190 mm	17'0"
Bucket Digging Force (ISO)	150 kN	38,811 lbf
Stick Digging Force (ISO)	106 kN	23,911 lbf

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2019 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

AEXQ2192-02 (01-2019)
Replaces AEXQ2192-01
Build Number: 07B
(North America, Europe, ANZ)

