



DECLARATION OF PERFORMANCE No 0297

1. Unique identification code of the product-type: **H40 EXTREME**
2. Intended use/es:
Improved reaction resin adhesive, all internal and external tiling
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 3
System 3 for reaction to fire
5. Harmonised standard: **EN 12004:2007 + A1:2012**
Notified body/ies: **Modena Centro Prove No. 1599**
Istituto Giordano No. 0407

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class B-s1,d0
Bond strength as: initial shear adhesion strength	≥ 2,0 N/mm²
Durability for: shear adhesion strength after thermal shock shear adhesion strength after water immersion	≥ 2,0 N/mm² ≥ 2,0 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 06/11/2017