



DECLARATION OF PERFORMANCE No. 0079

- 1. Unique identification code of the product-type: KERAKOVER ECO ACRILEX FLEX
- 2. Intended use/es:

Products for the protection of concrete structures, Ingress protection (1.3), moisture control (2.2) and increasing resistivity (8.2)

- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. System/s of AVCP: System 2+ and System 3 for reaction to fire
- Harmonised standard: EN 1504-2: 2004
 Notified body/ies: SGS Italia No. 1381

INSTYTUT CERAMIKI I MATERIALOW BUDOWLANYCH No. 1487

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class B-s1,d0
Permeability to CO ₂ Permeability to water vapour (S _D) Capillary absorption and permeability to water	S _D > 50 m Classe I; S _D < 5 m w ≤ 0,1 Kg/m² h ^{0,5}
Adhesion strength by pull-off test	≥ 0,8 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Romano Sghedoni (legal representative)

At Sassuolo, on 10/07/2019

Medei