



Overall Dimension  
12-3/4"  
325mm

3/4"  
19mm

Cutout Dimension  
11-1/4" ± 1/16"  
285 ± 1.6mm

3/4"  
19mm

**Installation Template and Instructions**  
Bobrick Model B-527 Waste-Disposal Door  
for 3/4" to 1-1/2" (19 to 38mm) Thick Countertops

Corners May Be  
Rounded to 1/8"  
3mm Radius

1. This unit was designed for countertops measuring 3/4" to 1-1/2" (19 to 38mm) mounting thickness.
2. Minimum space requirement: 6" x 12-3/4" (152 x 324mm). 4-1/2" (114mm) minimum clearance below mounting surface required for downward swing of waste door.
3. Cut out countertop to the dimension shown along the dotted line, making certain to position cutout in the location desired.
4. Apply sealant or caulk to underside of flange all around.
5. Place Waste Door into opening.
6. While holding unit down, snug against the countertop, bend (4) tabs up against underside of countertop. Secure with (4) screws provided.

Cutout  
Dimension  
4-1/2" ± 1/16"  
114 ± 1.6mm

Overall  
Dimension  
6"  
152mm



**BUILDING VALUE SINCE 1906**  
**BOBRICK.COM**

© 2015 by Bobrick Washroom Equipment, Inc.  
Form No. 527-69 r6/30/15 Printed in U.S.A.

**In the U.S.A.: BOBRICK WASHROOM EQUIPMENT, INC.**  
200 Commerce Drive, Clifton Park, New York 12065-1350 • Tel: (518) 877-7444 • FAX: 518-877-5029  
6901 Tujuna Avenue, North Hollywood, California 91605-5882 • Tel: (818) 982-9600 • FAX: 818-503-9287  
or email BobrickCustomerService@bobrick.com

**In Canada: BOBRICK WASHROOM EQUIPMENT COMPANY**  
45 Rolark Drive, Scarborough, Ontario M1R 3B1 • FAX: (877) 423-8555

Edge of Cutout