

CHARACTERISTICS

- An extruded round sealing strip with closed structure
- Odourless
- Physiologically neutral
- Good chemical resistance
- Completely CFC and HCFC free (ODP = 0)



APPLICATIONS

- Developed for use in static and moving joints with different expansion forms.
- It helps to reduce amount of sealant used and is intended as joint filler.
- Expansion joints in walls, glazing, partition walls
- Joints in paving and tiles, but also in prefabricated concrete or brick constructions
- Has been developed for use with cold sealing materials like : silicon-, polyurethane-, hybrid polymere-, polysulphide-, butyl-, thiokol- en acrylic sealants, etc.

TECHNICAL CHARACTERISTICS

Structure	PE foam with closed cells
Colour	Grey
Production	Completely CFC and HCFC free (ODP = 0)
Density	$\pm 25 \text{ kg/m}^3$
Water absorption : DIN 53495	<0,5 vol. %
Temperature resistance	-40°C - +100°C
Insulation value : ISO 10456	0,050 W/mK
Fire resistance : DIN 4102, Part 1	B2

PAKING AND MEASUREMENTS

Diameter	Profile	Packing	Joint width
6 mm	Full	1500 m	5 mm or less
8 mm	Full	900 m	6 mm or less
10 mm	Full	600 m	7 - 8 mm
13 mm	Full	400 m	9 - 10 mm
15 mm	Hollow	250 m	11 - 12 mm
20 mm	Hollow	150 m	13 - 17 mm
25 mm	Hollow	100 m	17 - 21 mm
30 mm	Hollow	80 m	22 - 26 mm

METHOD OF USE

Application

- Remove the foam strip directly from the user-friendly packaging.
- You need a blunt object to apply the strip.
- Place the foam strip at the depth recommended for the sealing material.
- Insert the sealing material according to instructions.